

OZO-10HDHF 200g/h Ozone Generator

FEATURES

- Air Cooled Patented Corona Cell
- 0-12 wt% Ozone Concentration
- Air or Oxygen Feed
- Stable Ozone Production
- Power Input Pilot Light
- Ozonation Pilot light
- Over-Temperature Protection
- Low Feed Gas Flow Protection
- Voltmeter
- Stainless Steel Ozone Fittings
- Ozone Resistant Check Valve
- Ozone Resistant Plumbing
- Easy Maintenance and Service
- Warranty: 1 Year parts and labor against manufacturing defects (see manual for details)
- Made In Canada

STANDARD CONTROLS

- Feed Gas Flow Meter

OPTIONAL FEATURES

- 4-20 mA or 0-10 VDC Input
- 0-100% Ozone Output Control
- Remote On/Off Control
- Voltage Surge Suppressor
- Air conditioned NEMA Enclosure
- Custom Controls available upon request



OZO-10HDHF SUMMARY

- The OZO-10HDHF ozone generator produces 200 g/h O₃ from oxygen feed and 100 g/h O₃ from dry air feed.
- It is suitable for a wide range of commercial and industrial applications ranging from water bottling to waste water treatment.
- The OZO-10HDHF can operate under suction, with a venturi for example, and under pressure using pressurized air or oxygen feed.
- This Canadian-made ozone generator meets the highest standards of workmanship, quality, efficiency and reliability.

SPECIFICATIONS

Ozone Output	200 gO ₃ /h with dry O ₂ feed 100 gO ₃ /h with dry air feed
Feed Gas Flow rate	Oxygen: 100-150 cfh @ 10 psi Air: 200-300 cfh @ 10 psi
Ozone Concentration	3.0 - 4.0 wt% at 200 gO ₃ /h with O ₂ feed depending on flow rate up to 12wt% possible
Standard Pressure	10 psi nominal, up to 30 psi max
Feed Gas Temperature	10C to 25C Max (50F to 77F)
Feed Gas Humidity	-40C dew point or drier
Dimensions (H x W x D)	Ozonator : 91 cm x 76 cm x 41 cm (36" x 30" x 16")
Power Consumption	Ozonator: 1250 W
Voltage	120VAC, 208VAC, 220VAC, 240VAC models available, 50/60 Hz
Ambient Temperature and Humidity	Temperature: 25C (77F), Relative Humidity: less than 50%

* Features and specifications subject to change without notice



600 Robitaille, Shefford, Quebec, J2M1X2, Canada Tel:450-378-6825 Fax: 450-777-0264
engineering@ozomax.com www.ozomax.com