

OZO-6SDHF 300g/h Ozone Generator

FEATURES

- Air Cooled Patented Corona Cell
- 0-12 wt% Ozone Concentration
- Air or Oxygen Feed
- Stable Ozone Production
- Power Input Pilot Light
- Ozonation Pilot light
- Over-Temperature Pilot Light
- Over-Temperature Protection
- Low Feed Gas Flow Protection
- Ammeter
- Voltage Surge Suppressor
- Stainless Steel Ozone Fittings
- Ozone Resistant Check Valve
- Ozone Resistant Plumbing
- Air conditioned NEMA Enclosure
- Easy Maintenance and Service
- Warranty: 1 Year parts and labor against manufacturing defects (see manual for details)
- Made In Canada

STANDARD CONTROLS

- Feed Gas Flow Meter
- Corona Cell Internal Pressure

OPTIONAL CONTROLS

- 4-20 mA or 0-10 VDC Input
- 0-100% Ozone Output Control
- Remote On/Off Control
- Custom Controls available upon request



OZO-6SDHF shown with back-mounted air conditioner (AC cannot be seen in picture). Top-mounted and side-mounted ACs also available.

OZO-6SDHF SUMMARY

- The OZO-6SDHF ozone generator produces 300 g/h O₃ from oxygen feed and 150 g/h O₃ from dry air feed.
- It is suitable for a wide range of commercial and industrial applications ranging from water bottling to waste water treatment.
- The OZO-6SDHF can operate under suction, with a venturi for example, and under pressure using pressurized air or oxygen feed.
- This Canadian-made ozone generator meets the highest standards of workmanship, quality, efficiency and reliability.

SPECIFICATIONS

Ozone Output	240-300 gO ₃ /h with dry O ₂ feed depending on flow rate 120-150 gO ₃ /h with dry air feed depending on flow rate
Feed Gas Flow rate	Oxygen: 150 cfh @ 10 psi, for 300 gO ₃ /h output 90 cfh @ 10 psi, for 240 gO ₃ /h output Air: 300 cfh @ 10 psi, for 150 gO ₃ /h output 180 cfh @ 10 psi, for 120 gO ₃ /h output
Ozone Concentration	4.8 wt% at 240 gO ₃ /h, 3.6 wt% at 300 gO ₃ /h up to 12wt% possible
Standard Pressure	10 psi nominal, up to 30 psi max
Feed Gas Temperature	10C to 25C Max (50F to 77F)
Feed Gas Humidity	-40C dew point or drier
Dimensions (H x W x D)	Ozonator : 107 cm x 91 cm x 41 cm (42" x 36" x 16") Overall including skid and AC: 142 cm x 112 cm x 107 cm (56" x 44" x 42")
Power Consumption	Ozonator: 1800 W Air conditioner: 760 W
Voltage	120VAC, 208VAC, 220VAC, 240VAC models available, 50/60 Hz
Ambient Temperature and Humidity	Temperature: 25C (77F), Relative Humidity: less than 50%

* Features and specifications subject to change without notice



600 Robitaille, Shefford, Quebec, J2M1X2, Canada Tel:450-378-6825 Fax: 450-777-0264
engineering@ozomax.com www.ozomax.com